WMGOA3PW022018

GO-A3-PW



GO-A3-PW HOPPER CAR GATE OPENER



1-800-842-7284 1-360-920-9411 Outside US & Canada www.chicagovibrator.com Solutions@chivib.com

WE FIND A WAY - OR MAKE ONE!

GO-A3-PW HOPPER CAR GATE OPENER



THE GO-A3-PW GENERATES A CONSTANT SPEED OF 8.5-RPM, AND A POWER OUTPUT OF 2,700 LB-FT.

SELF-CONTAINED, SLIDE-A-WAY OUTRIGGERS

Simply and safely counterbalances the torque reaction that occurs when opening or closing gates; improves maneuverability.

ADJUSTABLE HEIGHT HANDLE

Easily adjusts to the correct height and angle for operator preference and safe usage.

PIVOT WHEELS

Push/Pull valve allows pneumatic tires to manually pivot 90° to follow capstan movement on traveling gates.

CAPSTAN DRIVE FITTING

Heavy-Duty, bolt-on, 1-piece

construction to guarantee

long service life.

GO-A3-PW HOPPER CAR GATE OPENER

WE FIND A WAY - OR MAKE ONE!

SPECIFICATIONS	
MODEL	GO-A3-PW Pivot Wheel Gate Opener with
	Slide-A-Way Outriggers
POWER	Pneumatic; 18.5 CFM @ 90 PSI
WORKING TORQUE	2,700 lb-ft constant at 8.5-RPM
WHEEL ASSEMBLY	10.5″ Dia with 4.10/3.50-4″
	Pneumatic Tubeless Tires, Sawtooth Tread
FRAME DIMENSIONS	36″D x 36″W x 46″H
HANDLE WIDTH	36" Wide; Fitted with Handle Grips
HEIGHT ADJUSTMENT	Height Adjustable: 7.5" to 19.75" Ground to
	Capstan
INLET COUPLING	Universal Coupling (Chicago Type) w/ Safety
	Lock Pin
FINISH COATING	Acrylic Enamel Coat Finish
LUBRICATOR CAPACITY	4.5 oz
INCLUDED	(1) Filter, Regulator w/Gauge, Lubricator
	Trio-Control; (1) Drive Fitting; (1) Qt TOOL
	LUBE [™] Air Tool Oil; (1) Operating Video; (1)
	Manual
GATE OPENER WEIGHT	285 lbs
SHIPPING WEIGHT	465 lbs

Workmaster[®] line of Hopper Car Unloading Products

ranging from our wide selection of gate openers and railcar vibrators to our railcar pocket-to-undertrack conveyor connectors, offers total solutions to the vexing problems of unloading hopper cars.



OPERATES ON ONLY 18.5 CFM AT 90 PSI (120 PSI MAX)

To provide energy efficient force output at a constant RPM.

OPERATES AT 83 dBA

To accommodate noise restrictions at plant and unloading site operations.

ADJUSTABLE HEIGHT OPERATING MECHANISM

To easily compensate for differing height gates, or variations in unloading site decks or platforms.

SMOOTH, CONTROLLED FORCE

To facilitate steady gate opening without concern for wear of gate mechanism.

ONE-WORKER POSITIONING AND OPERATION

To enable greater productivity and reduced man- power planning.

ECONOMICAL TO PURCHASE

To meet even the tightest budget when a wheeled cart gate opener is required.

HEAVY-DUTY STEEL TUBE FRAME

To withstand the rugged operating conditions at unloading sites.

DURABLE WHEEL & PNEUMATIC TIRE ASSEMBLIES

To easily maneuver over rough rail-side conditions.

WE FIND A WAY — OR MAKE ONE!

WORKMASTER[®] is a manufacturer of labor savings bulk material handling tools to help safely and efficiently unload, transport, store and process bulk solids from hopper bottom railcars, bulk trailers, bins, silos and chutes. To help Customers gain maximum benefit from our bulk materials handling tools and equipment, we also supply a complete line of operating, mounting, and maintenance products and accessories, such as Timers and Motor Controls, Vibrator Mounts, and Lubricating Oils to help keep your unloading site tools running longer and more efficiently. WORKMASTER products help Customers work more safely and efficiently, increase the lifespan of production-critical equipment, and decrease operating and maintenance costs of tools and equipment used in some of Industry's most dangerous, difficult, and dirty jobs.

GO-A3-PW



ChicagoVibratorProducts Flow and Compaction

1-800-842-7284 1-360-920-9411 Outside US & Canada www.chicagovibrator.com Solutions@chivib.com