




**Oscillator Vibrator** - Flexible linear force vibrator with an external weight which allows vibration force and frequency to be adjusted; recommended for feeder applications.

### SPECIFICATIONS

MODEL	AIR CONSUMPTION CFM			FREQUENCY VPM			FORCE LBS			WORKING MOMENT LBS/FT		
	PRESSURE PSI			PRESSURE PSI			PRESSURE PSI			PRESSURE PSI		
	30	60	90	30	60	90	30	60	90	30	60	90
VOA-32	0.28	0.035	1.04	2050	2900	3400	2.70	6.70	9.50	.0003	.0004	.0004
VOA-70	0.70	1.40	2.10	1420	1900	2250	13.50	31.50	46.20	.0030	.0036	.0036
VOA-100	1.40	3.83	5.40	1130	1550	2020	27.00	59.70	119.40	.0077	.0092	.0085
VOA-140	2.60	7.65	12.20	1240	1500	2050	46.20	76.60	147.50	.0134	.0148	.0202

### DIMENSIONS



MODEL	DIMENSIONS (INCHES)									
	A	B	C	D	E	F	G	H	J	K
VOA-32	1.26	3.58	0.85	0.20	0.79	M5	M5	M6	0.31	M5
VOA-70	1.65	4.57	1.01	0.31	1.93	1/8"	1/8"	M10	0.71	M10
VOA-100	2.05	5.43	1.36	0.28	1.97	1/4"	1/4"	M16	0.98	M16
VOA-140	2.24	5.51	1.41	0.47	2.87	1/4"	1/4"	M16	1.57	M16